

# HSLIS e-Series

Liquid Optical Particle Counter



The HSLIS e-Series (High Sensitivity Liquid In Situ) particle counter provides continuous, real-time monitoring of contamination levels in DI water and process chemicals. The combination of high sensitivity and low cost makes it ideal when large numbers of sensors and/or long term trending are required.

The HSLIS e-Series has sizing sensitivity down to 0.05  $\mu\text{m}$  in DI water and 0.065  $\mu\text{m}$  in process chemicals.

Integration of the HSLIS e-Series into Particle Measuring Systems' Facility Net software provides an economical way to monitor multiple flow systems and provide dedicated local display and control capabilities.

## BENEFITS

### Cost-Effective

- Monitor for long term trends in fluid quality
- Lower overall costs with the control and monitoring of multiple particle counters with Ethernet networks
- Low initial capital investment and lower maintenance cost with proven reliability of the HSLIS design

### HSLIS e-Series with Facility Net

- Existing network can be utilized with Ethernet communication to Facility Net software
- Tabular and statistical process control (SPC) charts for detailed statistical information
- Alphanumeric paging and e-mailing functions to alert operator of data excursions
- Sensor status displays four-level alarm for monitoring out-of-spec condition
- Simplified data interpretation with real-time and retrieved data time plots

## APPLICATIONS

- Quantifying particle concentrations in DI water systems
- Monitoring chemical delivery systems
- Measuring filter efficiency
- Detecting bacterial growth in DI water systems
- Episodic event tracking and alarming
- Continuous system monitoring

# HSLIS e-Series

Liquid Optical Particle Counter

Specifications

	M50e	M65e	M100e
Size range	0.05 – 0.2 µm	0.06 – 0.2 µm	0.1 – 1.0 µm
Channels	4		
Channel sizes	0.05, 0.1, 0.15, 0.2 µm	0.065, 0.1, 0.15, 0.2 µm	0.1, 0.2, 0.5, 1.0 µm
Flow rate	100 ml/min ± 10%	100 ml/min ± 10%	300 ml/min ± 10%
Sample volume	0.25 ml/min	0.6 ml/min	3.0 ml/min
Counting efficiency	100% of sample volume		
Maximum concentration	10,000 counts/ml		
Sample temperature	194 °F (90 °C)	302 °F (150 °C)	302 °F (150 °C)
Zero count	< 1000 counts/liter	< 2000 counts/liter	< 1000 counts/liter
Wetted surface materials	Delrin®, Kalrez® 4079, Kel-F®, Teflon®, Viton®, fused silica	Kalrez 4079, Kel-F, Teflon, sapphire	Kalrez 4079, Kel-F, Teflon, sapphire
Dimensions (l, w, h)	21 x 10.75 x 7 in (53 x 27 x 18 cm)		
Weight	28 lb (13 kg)		
Power	85 – 250 VAC, 50 – 60 Hz		
Calibration	Materials used are traceable to US National Institute of Standards and Technology (NIST) and/or Japanese Institute of Standards (JIS).		
Environment	Temperature: 50 – 95 °F (10 – 35 °C); Humidity: non-condensing		
Communications	Ethernet, 4-20 mA (5 outputs; 4 particle channels, 1 instrument status) RS-232 (set-up and diagnostics, no data)		

\*Greater than 90% accuracy (less than 10% coincidence loss) at maximum recommended concentration.

## HEADQUARTERS

5475 Airport Blvd  
Boulder, Colorado 80301 USA  
T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support  
T: +1 800 557 6363  
Customer Response Center  
T: +1 877 475 3317  
E: info@pmeasuring.com

## GLOBAL OFFICES

BRAZIL  
T: +55 11 5188 8227  
E: pmsbrazil@pmeasuring.com

CHINA  
T: +86 21 6113 3600  
E: pmschina@pmeasuring.com

Teflon® is a registered trademark of The Chemours Company, FC, LLC.  
Delrin®, Kalrez® and Viton® are registered trademarks of DuPont.  
Kel-F® is a registered trademark of 3M.  
All other trademarks are the property of their respective owners.  
Particle Measuring Systems, Inc. reserves the right to change specifications without notice.  
© 2016 Particle Measuring Systems, Inc.  
All rights reserved.

FRANCE  
T: +33 (0)6 82 99 17 98  
E: pmsfrance@pmeasuring.com

GERMANY  
T: +49 6151 6671 632  
E: pmsgermany@pmeasuring.com

ITALY  
T: +39 06 9053 0130  
E: pmsrl@pmeasuring.com

JAPAN  
T: +81 3 5298 8175  
E: pmsjapan@pmeasuring.com

KOREA  
T: +82 31 286 5790  
E: pmskorea@pmeasuring.com

MEXICO  
T: +52 55 2271 5106  
E: pmsmexico@pmeasuring.com

NORDIC  
T: +45 707 028 55  
E: pmsnordic@pmeasuring.com

PUERTO RICO  
T: +1 787 718 9096  
E: pmspuertorico@pmeasuring.com



**PARTICLE  
MEASURING  
SYSTEMS®**

SINGAPORE  
T: +65 6496 0330  
E: pmsingapore@pmeasuring.com

SWITZERLAND  
T: +41 71 987 01 01  
E: info@cas.ch

TAIWAN  
T: 886-3-5525300 Ext: 301  
E: pmstaiwan@pmeasuring.com

UNITED KINGDOM  
T: +44 1684 581 000  
E: pmsemea@pmeasuring.com